

3.
3.1.

3.1.1

	3360	3361	3363	3366	3367	3368
	6000					
	2					
			.			
	«OL»					
	BAT					
	9 ()					
	25					
	30					
	229 80 49					
	303					
	-10 .50° / 90%	-10 .50° / 90%	-10 .50° / 90%	5°40° / 80%	-10 .50° / 90%	5°40° / 80%
	-30 .. 60° / 90%	-30 .. 60° / 90%	-30 .. 60° / 90%	-2060° / 80%	-30 .. 60° / 90%	-2060° / 80%

3.2

3.2.1

(23±5)° , . . .	: ≤75%	DT-3360	DT-3361	DT-3363	DT-66	DT-3367	DT-3368
		60 , 600 , 1000			660/1000	60/600/1000	660/1000
		±(2,0%+5 . . .)		±(3,0%+5 . . .)	±(2,8%+10 . . .)	±(3,0%+5 . . .)	±(2,5%+10 . . .)
		0,01			0,1	0,01	0,1
		50-400					
			60/600/1000		60/600/1000	660/1000	
			±(2,8%+8 . . .)		±(2,8%+8 . . .)	±(2,5%+10 . . .)	
			0,01		0,01	0,1	
		6/60/600/750	0,6/6/60/600/750	0,66/6,6/66/600	0,6/6/60/600/750	0,66/6,6/66/600	

		$\pm(1,5\%+5 \dots)$	$\pm(0,8\%+20 \dots)$	$\pm(1,0\%+10 \dots)$	$\pm(0,8\%+20 \dots)$	$\pm(1,8\%+10 \dots)$
		1	100	1	100	1
		0,6/6/60/600/1000	0,6/6/60/600/800	0,66/6,6/66/600	0,6/6/60/600/800	6,6/66/600
		$\pm(0,8\%+3 \dots)$				$\pm(1,5\%+3 \dots)$
		100		1	100	1
		600 , 6/60/600 , 6/60	0,66/6,6/66/600 6	600 , 6/60/600 6/60	0,66/6,6/66/660 , 6,6/66	
		$\pm(1,0\%+4 \dots)$				
		0,1				
		40/400 , 4/40/400/4000	40/400 , 4/40/100	6,6/66/660 , 6,6/40	40/400 , 4/40/100	
		$\pm(3,5\%+10 \dots)$	$\pm(3,0\%+5 \dots)$	$\pm(3,0\%+5 \dots)$	$\pm(3,0\%+5 \dots)$	
		0,01		1	0,01	
		10/100/1000 , 10/100/1000 , 10		30 15	10/100/1000 , 10/100/1000 10	30 15
		$\pm(1,2\%+2 \dots)$				
		0,001		1	0,001	1
			0,5~99,0%	10~94,9%	0,5~99,0%	10~94,9%
		$\pm(1,2\%+2 \dots)$				
			-20° ~760°			
			$\pm(3,0\%+5^\circ)$			
		< 100		<40	< 100	< 40
		0,3		0,5	0,3	0,5

4.

4.1

		1	
		2	
		1	
		1	9 « »
		1	
		1	
(-)		1	: 3363/61/67/68/66
		1	: 3363/61/67/68/66

5.

5.1.

5.1.1

	DT-3360/63	
MODE		
RANGE		
MAX/MIN		/
Hz%		%